

SPECIFICATION & PROCEDURAL DATA SHEET

ECOWOODOIL - GARDEN FURNITURE OIL

- DESCRIPTION:** A low sheen finishing oil that penetrates the timber substrate to nourish, preserve and seal; as well as providing protection against weather degradation and rot.
- INGREDIENTS:** Filtered, unmodified Tung Nut Oil, Citrus, Eucalypt and Pine Wood oils/extracts with dissolved, refined Bees Wax.
- USES:**
Exterior – Preserving and finishing timber garden furniture, shutters, louvres, gun stocks, spa panelling and may be used on joinery under full verandah protection. Also suitable for Marine use i.e. trims/hand-rails & small decking areas on boats.
Internal – Timber bench tops and vanities in wet areas ie. bathrooms & laundries. The ingredients in this product best address their needs, **though not to be used on flooring**.
- SPECIAL NOTES:**
- To test timber for oil application suitability – sprinkle water onto timber, if water beads or sits on top **do not use oil**; if water is absorbed into the timber it is suitable for oil application following can instructions.
 - With new garden furniture settings—many are supplied pre-treated with solutions containing biocides (volatile chemicals insecticide/fungicides) which can react with Tung Oil causing surface whitening. If this occurs, and to rectify, apply more oil and agitate affected areas with a green synthetic scourer (Scotchbrite) then rub over with clean cloth.
 - Previously finished settings which have remains of the prior finish evident would need to be entirely sanded down before oiling.
 - Always oil in the morning, and leave setting to dry, under cover, and with good ventilation.
 - To restore weathered timbers that have lost their original colour consider **ECOWOODOIL GARDEN FURNITURE OIL-Golden Teakwood Enhancer or Red Hardwood Enhancer**
The Enhancers will provide longer lasting protection to furniture fully exposed to sunlight.
- APPEARANCE:** A matt, clear finish accentuating the natural colour & character of the timber.
- STAINING:** This product is a penetrative, finish and should NOT have other brands of pigment/colourants added or used under it.
- SIZES AVAILABLE:** 500ml, 1 ltr, 2 ltr cans. For availability visit website home page.
- | COVERAGE: | APPROX. PER COAT |
|-----------|------------------------|
| Softwoods | 6-8 sq. metres/litre |
| Hardwoods | 12-16 sq. metres/litre |
- PREPARATION:**
- Refer again to the **Special Notes** above.
 - Ensure timber surfaces are clean and dry (Refer timber preparation sheet)
 - If surfaces are rough/furry, sand off excess fibre with **220- 340** grit sandpaper then dust off prior to oiling.
- APPLICATION:**
- Ensure you have read & understood aforementioned **usage, notes** and **preparation** advice first. **If skin-sensitive wear oil-impervious gloves**. Ensure good ventilation.
 - Shake/stir well prior and during use – this maintains an even distribution of ingredients throughout.
 - Using a brush or applicator apply **2** (two) coats a minimum of **24** hours apart (**1** coat only when rejuvenating) **always** dry brush or cloth in excess surface oil within **1** (one) hour of **each** application. Excess oil if left on the surface will remain tacky, mark and stain easily .
- CLEAN UP:** Hot, soapy water or Gum Turpentine.
- MAINTENANCE:**
- Cleaning before oiling, or where necessary: wet timber surfaces with water first, then scrub with warm soapy water (an Alkaline salts cleaner is recommended), rinse thoroughly, then allow to dry for a minimum of **24-48** hours prior to oiling.
 - If timber surfaces are rough/furry after cleaning, sand off excess fibres with **120-180** grit sand paper before oiling.
 - A one coat application (clothed in) every **3- 6** months in exposed conditions and every **6 – 9** months when under protected location.
- BOTTOM LINE:** Finally, you are not excused from referring to can's instruction label for other storage, disposal, health and safety considerations.

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF THESE PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS ARE MADE WITHOUT GUARANTEE. NO REPRESENTATIVE OR AGENT OF OURS HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

ECOWOODOIL packed under licence by **ORGANOIL PTY. LTD. ABN 62 052 501 792 PO Box 377 Byron Bay, NSW AUSTRALIA 2481**
PH: 6685 5393 FAX: 6685 6747 - WEB SITE: www.ecowoodoil.com